KC ULTRA

Upgrade to the KC ULTRA modular building door



Manufactured in our own factory - ALWAYS HIGH QUALITY AND CONSISTENCY OF SUPPLY

Superior Kirncroft glazing system - NO MORE LEAKS

304-grade stainless steel hinges - NO MORE RUST

Heavy duty zinc-galvanised hinge reinforcing plate - NO MORE RUST

Fully welded hinge reinforcing plates - NO MORE BROKEN HINGE PLATES

Stainless steel screws - NO MORE RUST

Pre-marked fixing holes for door closer and chain restrictor - NO MORE MEASURING OR TEMPLATES

Shipped in welded steel crates - EASY STORAGE, EASY TO MOVE, EASY TO STACK, NO MORE DAMAGE

Drip guard fixes through door frame fixing holes - FASTER AND MORE EFFICIENT INSTALLATION

Optional Internal fixing holes - FIX THROUGH THE SIDE OF THE FRAME FOR MORE SECURITY

Size Specification

Rough opening: 36" x 80"

Door size: 34-3/4" x 78-5/8" x 1-3/4" Exterior flange: 38-1/2" x 82-3/4" Interior frame size: 35-5/8" x 79-3/4"

Technical Specification

Assembly: Pre-hung door and frame

Door: 20 GA galvanealed

Frame: 16 GA galvanealed fully welded Lock Prep: 161 lock & deadbolt Strike Prep: Matches lock & deadbolt

Hinges: 304 grade stainless steel with tamper-proof stainless steel pins

Hinge fixing plate: Heavy duty zinc-galvanized

Fully welded

Screws: Stainless steel throughout

Hardware reinforcing plates - 14GA galvanized steel for fixing closers and chains.

Fire exit push bar fixing plate - 14GA galvanized steel

Insulation: Polystyrene Core

Threshold: Aluminum ADA compliant threshold

Paint: Color matched to Sherwin Willams 701645 (RAL 9003)

Weather seal - Advanced profiled sealing system **Drip guard** - Color matched 18GA galvanized steel

Door sweep - Included

Shipping - Shipped in steel crates of 9 doors







